How does the LIADSmart ColorSave®1000 Gravimetric Feeder compare to your feeder	ColorSave ? 1000	Your Brand
Smart Clean self-cleaning feature purges material from hopper & screw using compressed air		0
Outer shell protects load cell & weigh hopper from vibrations & impacts	•	
Inner hopper with single, isolated load cell for precise do	sing	
3 hopper capacities/9 screw sizes for a wide range of applications from 0.25 - 440lbs/hr		
Variety of neckpieces accommodate multiple applications/mounting up to 4 feeders		
Single control for injection, extrusion, and extrusion blow-molding		
All stainless steel material contact points	•	
Network ready for real-time reporting & data collection	•	
Self-calibrating – saves time and ensures accurate dosing	•	
Stores up to 1,000 recipes for easy job recall & consisten	су	
5-year warranty		
Venturi loader attached to outer shell, not weigh hopper	Isolated inner protected weigh hopper	
Outer protective shell Spiral structure screws vs. smooth	Single point load cell, protected inside	
No gap between throat and feeder	Quick purging between re	uns
	Independent control with touc interface and mounting bracker	
	menace and mounting bracke	ι

Discover how ColorSave l000 can save labor and streamline production.

Vince Paskie, Business Development Manager, LIAD Smart Vince.Paskie@ampacet.com 914.715.0612 ci.systems@ampacet.com ampacet.com



